



The sample swatches shown are indications only and may vary from the original source. For exact references please request a swatch card. To order samples please contact: Wave Office Ltd. or visit [www.wave-office.co.uk](http://www.wave-office.co.uk)




Sandstorm YP107




Apple YP108




Parasol YP109




Bluebell YP097




Solano YP110




Nougat YP111




Campechc YP112



Scuba YP082




Bluefield YP021




Olympic YP113




Blizzard YP081



Windjammer YP047



Curacao YP005




Gayman YP024




Lobster YP076




Paseo YP081



Rainforest YP114




Ocean YP100




Tarot YP084



Jamaica YP027



Sombrero YP046



Monsterrat YP011




Costa YP026




Guyana YP051




Calypso YP106



Havana YP009




Taboo YP045



Arawak YP016



Tobago YP030



Belize YP105

**Composition:** 100% Polyester. Non metallic dyestuffs. **Weight:** 270g/m2  $\pm$ 5% (380g/lin.m.  $\pm$ 5%). **Width:** 140cm  $\pm$ 2% Usable **\*Abrasion Resistance:** 100,000 Martindale cycles with a 5 year guarantee of wearability (full details available). **Flammability:** BS EN 1021 - 1:2006 (cigarette), BS EN 1021 - 2:2006 (match), BS 7176 : 2007 Low Hazard. Note: Flammability performance is dependent on foam used. **\*Light Fastness:** 6 (ISO 105 - B02:1999). **\*Fastness to Rubbing:** Wet: 4 Dry: 4 (ISO 105 - X12:2002). **Maintenance:** Washable to 60°C. Vacuum regularly. Wipe clean with a damp cloth or shampoo using proprietary upholstery shampoo. **Availability:** Generally ex-stock. **Colour Matching:** Batch to batch variations in shade may occur within commercial tolerances.

\*Tested in accordance with BS2543:1995/2004. Further information available on request. Please note that ultimate seam performance is dependent on seam construction, and needle and thread type. We recommend that appropriate sewing advice be taken. Note: We reserve the right to alter technical specifications without notice.